

Model:RS-GX15D4/D2  
38 CM Subwoofer Speaker



SPECIFICATIONS

General Data		Unit
Overall Dimensions	394x218	mm
Nominal Power Handling	1500	W
Maximum Power	3000	W
Sensitivity	98.7	db
Frequency Response	30-500	Hz
Cone Material	Non Pressed Paper Cone	
Basket	Steel	
Net Weight	8	kg
Electrical Data		
Nominal Impedance	4X2/2X2	ohm
DC Resistance	3.6X3.6/1.8X2	ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	60.1	mm
Voice Coil Height	64	mm
HE magnetic Gap Height	30	mm
Voice Coil bobbin	AL	
Number of Layers	4L	
Magnet System Type	Ferrite	
T-S Parameters		
Suspension Compliance	0.16/0.13	Cms
Mechanical Q Factor	4.92/4.83	Qms
Electrical Q Factor	0.71/0.68	Qes
Total Q Factor	0.62/0.58	Qts
Moving Mass	155/162	Mms
Eq.Cas AIR Load	131/138	Vas
Resonant Frequency	31.9/31.5	Fs
Effective Piston Area	764.5cm <sup>2</sup>	SD

FEATURES

- \* Steel Basket
- \* Non Pressed Paper Cone With Foam Surround
- \* High Temperature 2.5 " Voice Coil
- \* Ferrite Magnet Structre

Dimensions

