

SPECIFICATIONS

General Data			Unit	FEATURES
Overall Dimensions	Ø102x 60	mm		Steel Basket
Nominal Power Handling	60W	W		Woolen & Paper Composite Cone, Treated Cloth Surround
Maximum Power	120W	W		Paper Dustcap
Sensitivity	90	dB		High Temperature CCAW 1" Voice Coil
Frequency Response	280~20000	Hz		High Performance 12.6oz Ferrite Magnet Structure
Cone Material	Woolen & Paper Composite			
Basket	Steel			
Net Weight	0.84	kg		
Electrical Data				
Nominal Impedance	4	Ohm		
DC Resistance	3.2	Ohm		
Voice Coil and Magnet Parameters				
Voice Coil Diameter	25.5	mm		
Voice Coil Height	6.5	mm		
Magnetic Gap Height	5	mm		
Voice Coil Robbin	Kapton			
Number of Layers	2			
T-S Parameters				
Suspension Compliance	83.977µM/N	Cms		
Mechanical Q Factor	6.938	Qms		
Electrical Q Factor	1.862	Qes		
Total Q Factor	1.468	Qts		
Moving Mass	3.676	Mms		
Eq. Cas AIR Loaded	0.332L	Vas		
Resonant Frequency	286.438Hz	Fs		
Effective Piston Area	52.783cm ²	SD		

Dimensions



