

Model:RS-M68AX  
16 CM Mid-Range Speaker



SPECIFICATIONS

General Data		Unit
Overall Dimensions	171x78	mm
Nominal Power Handling	250	W
Maximum Power	500	W
Sensitivity	96	db
Frequency Response	110-12K	Hz
Cone Material	Pressed Paper Cone	
Basket	Aluminum	
Net Weight	3.3	kg
Electrical Data		
Nominal Impedance	4	ohm
DC Resistance	3	ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	44.7	mm
Voice Coil Height	8	mm
HE magnetic Gap Height	7	mm
Voice Coil bobbin	KSV	
Number of Layers	2L	
Magnet System Type	Ferrite	
T-S Parameters		
Suspension Compliance	0.19	Cms
Mechanical Q Factor	4.03	Qms
Electrical Q Factor	0.35	Qes
Total Q Factor	0.32	Qts
Moving Mass	9.6	Mms
Eq.Cas AIR Load	6.2	Vas
Resonant Frequency	96	Fs
Effective Piston Area	153.9cm <sup>2</sup>	SD

FEATURES

- \* Aluminum Basket
- \* Pressed Paper Cone With Treated Cloth Surround
- \* High Temperature 1.75" Voice Coil
- \* Ferrite Magnet Structure

Dimensions

