





Model: RS-M8WK
20CM COAXIAL SPEAKER
1.5" Voice Coil / 4Ω

SPECIFICATIONS

General Data			Unit	FEATURES
Overall Dimensions	Ø 210 x 85	mm		Steel Basket
Nominal Power Handling	200	W		Paper Cone With Rubber Surround
Maximum Power	400	W		High Temperature 1.5" Aluminium Voice Coil
Sensitivity	92	dB		High Performance Neodymium Magnet
Frequency Response	55-20000	Hz		1" Voice Coil, PEI Diaphragm Tweeter
Cone Material	Paper			Dimensions 
Basket	Steel			
Net Weight	1.05	kg		
Electrical Data				
Nominal Impedance	4	Ohm		
DC Resistance	3.2	Ohm		
Voice Coil and Magnet Parameters				
Voice Coil Diameter	38.6	mm		
Voice Coil Height	10	mm		
Magnetic Gap Height	6	mm		
Voice Coil Bobbin	Aluminium			
Number of Layers	2L			
T-S Parameters				
Suspension Compliance	287.99µM/N	Cms		
Mechanical Q Factor	2.41	Qms		
Electrical Q Factor	0.331	Qes		
Total Q Factor	0.291	Qts		
Moving Mass	27.639 g	Mms		
Eq. Cas AIR Loaded	18.697 Ltr	Vas		
Resonant Frequency	56.412 Hz	Fs		
Effective Piston Area	21.382 cm ²	SD		