

**Model: RS-MB10K**

**26CM Mid-Bass Speaker**



**SPECIFICATIONS**

General Data			Unit	FEATURES
Overall Dimensions	260 x 127	mm		Aluminum Basket
Nominal Power Handling	600	W		Non-Pressed Paper Cone, Cloth Surround
Maximum Power	1200	W		Dome Paper Dust Cap
Sensitivity	96	dB		High Temperature Copper Voice Coil
Frequency Response	60~3000	Hz		93oz Ferrite Magnet Structure
Cone Material	Non-Pressed Paper			
Basket	Aluminium			
Net Weight	6.62	kg		
<b>Electrical Data</b>				
Nominal Impedance	4 / 8	Ohm		
DC Resistance	3.2 / 5.1	Ohm		
<b>Voice Coil and Magnet Parameters</b>				
Voice Coil Diameter	60.6	mm		
Voice Coil Height	16	mm		
Magnetic Gap Height	10	mm		
Voice Coil Robbin	TIL			
Number of Layers	1+1 L			
<b>T-S Parameters</b>				
Suspension Compliance	163.899/165.308μM/N	Cms		
Mechanical Q Factor	2.472/2.433	Qms		
Electrical Q Factor	0.209/0.224	Qes		
Total Q Factor	0.192/0.205	Qts		
Moving Mass	45.266g/45.5g	Mms		
Eq. Cas AIR Loaded	29.920L/27.599L	Vas		
Resonant Frequency	58.431Hz/60.045Hz	Fs		
Effective Piston Area	342.89cm <sup>2</sup>	SD		

**Dimensions**

