

General Data			Unit	Features
Overall Dimensions	205*90		mm	20 CM MIDRANGE SPEAKER
Nominal Power Handling	150		W	BLACK PAPER CONE WITH CLOTH EDGE
Maximum Power	300		W	IMPEDANCE: 4 Ω
Sensitivity	93,5		dB	RATED POWER: 150W
Frequency Response	100-15K		Hz	MAX. POWER: 300W
Cone Material	PAPER CONE			FREQUENCY RESPONSE: 100-15KHZ
Basket	METAL			SENSITIVITY: 93.5DB
Net Weight	1,67		kg	Dimensions
Electrical Data				
Nominal Impedance	4		Ohm	
DC Resistance	3,2		Ohm	
Voice Coil and Magnet Parameters				
Voice Coil Diameter	$\Phi 30.5$		mm	
Voice coil wire	KCCAW			
Voice Coil Height	8,5		mm	
Magnetic Gap Height	5		mm	
Magnet system type	High Flux Ferrite			
Voice Coil Bobbin	KAPTON			
Number of Layers	2L			
T-S Parameters				
Suspension Compliance	0,1478		Cms	
Mechanical Q Factor	7,75		Qms	
Electrical Q Factor	1		Qes	
Total Q Factor	0,88		Qts	
Moving Mass	14,5891		Mms	
Eq. Cas AIR Loaded	11,1393		Vas	
Resonant Frequency	108,4		Fs	
Effective Piston Area	2,32E+02		SD	

