

General Data		Unit	Features
Overall Dimensions	235*103.8	mm	6x9" COAXIAL SPEAKER
Nominal Power Handling	170	W	BLACK PAPER CONE WITH FOAM EDGE
Maximum Power	340	W	IMPEDANCE: 4 Ω
Sensitivity	92	dB	RATED POWER: 170W
Frequency Response	60-20K	Hz	MAX. POWER: 340W
Cone Material	PAPER CONE		FREQUENCY RESPONSE: 60-20KHZ
Basket	METAL		SENSITIVITY: 92DB
Net Weight	1,5	kg	Dimensions

Electrical Data

Nominal Impedance	4	Ohm
DC Resistance	3,2	Ohm

Voice Coil and Magnet Parameters

Voice Coil Diameter	Φ 30.5	mm
Voice coil wire	SV	
Voice Coil Height	9,5	mm
Magnetic Gap Height	4	mm
Magnet system type	High Flux Ferrite	
Voice Coil Bobbin	KAPTON	
Number of Layers	2L	

T-S Parameters

Suspension Compliance	0,4875	Cms
Mechanical Q Factor	11,63	Qms
Electrical Q Factor	0,81	Qes
Total Q Factor	0,75	Qts
Moving Mass	14,4065	Mms
Eq. Cas AIR Loaded	32,6569	Vas
Resonant Frequency	60,06	Fs
Effective Piston Area	2,19E+02	SD

